

View Online at <https://aerobasegroup.com/nsn/5930-00-007-9269>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.312 inches single mounting facility

**Overall Length:**

3.828 inches

**Overall Height:**

1.828 inches

**Overall Width:**

1.609 inches

**Shaft Diameter:**

0.266 inches 1st actuator and 0.268 inches 1st actuator

**Shaft Length:**

0.906 inches 2nd actuator

**Nonturn Device Radius:**

0.531 inches at 3:00 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Pin at 3:00 o'clock

**Operating Temperature Range:**

-65.0 to 125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

13 1st actuator

**Shaft Type:**

Round, slotted 1st actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees 2nd actuator

**Detent Rotational Torque Range:**

+2.000 to 2.500 inch-pounds 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0