NSN 5930-00-008-4372

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-008-4372

Thread Class: 2b 1st mounting facility Thread Length: 0.500 inches 2nd mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 13.095 inches **Overall Height:** 2.297 inches **Overall Width:** 2.297 inches **Shaft Length:** 2.532 inches single actuator **Individual Section Quantity:** 23 **Longest Horizontal Distance Between Mounting Centers:** 2.297 inches 1st mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches 1st mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 7 each section rear **Mounting Method:** Threaded stud 2nd mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 1st mounting facility **Thread Size:** 0.190 inches 2nd mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular 2nd mounting facility **Switch Actuator Indexing Position Quantity:** 8 single actuator **Shaft Type:**

Rectangular/square, threaded hole single actuator

NSN 5930-00-008-4372Rotary Switch - Page 2 of 2



Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea level
Style Designator:
Tap, circuit selector
Test Data Document:
81349-mil-s-21604 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf 2nd mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0
Mil-std (military Standard):
Mil-s-21604 spec.