

View Online at <https://aerobasegroup.com/nsn/5930-00-008-4378>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

4.329 inches

Overall Height:

0.937 inches

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

1.023 inches 2nd actuator

Individual Section Quantity:

6

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 3rd section front

Throw Quantity:

8 3rd section front

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor provisions

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

12 1st actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 6th section rear

Switch Actuator Positioning Increment:

30.0 degrees 1st actuator

Detent Rotational Torque Range:

+15.000 to 35.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Fixed stop 1st actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0