

View Online at <https://aerobasegroup.com/nsn/5930-00-008-4467>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.250 inches single mounting facility

**Overall Length:**

2.813 inches

**Overall Height:**

1.843 inches

**Overall Width:**

1.718 inches

**First Flat Length:**

0.250 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.688 inches single actuator

**Nonturn Device Radius:**

0.531 inches at 1: 30 o'clock

**Individual Section Quantity:**

3

**Nonturn Device Type:**

Tab at 1: 30 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

16 single actuator

**Shaft Type:**

Round, flatted single actuator

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

20.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Special Features:**

Weapon system essential

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0