

View Online at <https://aerobasegroup.com/nsn/5930-00-008-8456>

**Overall Length:**

3.156 inches

**Overall Height:**

2.438 inches

**Overall Width:**

2.688 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.375 inches

**Longest Vertical Distance Between Mounting Centers:**

0.500 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Capillary tube end seal connection

**Contact Action Stimulus:**

Decrease

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

8.0 amperes resistive load first voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+5.00 to 150.00 actuation point pounds per square inch and +5.00/+150.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Voltage Rating In Volts:**

240.0 ac at sea level first voltage

**Special Features:**

Two extra mtg holes in center of mtg bracket

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Ptf-sae short single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0