

View Online at <https://aerobasegroup.com/nsn/5930-00-008-8456>

Overall Length:

3.156 inches

Overall Height:

2.438 inches

Overall Width:

2.688 inches

Unthreaded Mounting Hole Diameter:

0.156 inches

Longest Horizontal Distance Between Mounting Centers:

2.375 inches

Longest Vertical Distance Between Mounting Centers:

0.500 inches

Pressure Switch Type:

Differential

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Capillary tube end seal connection

Contact Action Stimulus:

Decrease

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary

Terminal Type:

Tab w/screw

Contact Load Current Rating:

8.0 amperes resistive load first voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+5.00 to 150.00 actuation point pounds per square inch and +5.00/+150.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

240.0 ac at sea level first voltage

Special Features:

Two extra mtg holes in center of mtg bracket

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0