## NSN 5930-00-009-4437

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-009-4437

## Thread Length:

0.469 inches single mounting facility

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

**4.376 inches** 

First Flat Length:

0.750 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.969 inches single actuator

**Overall Diameter:** 

2.000 inches

**Individual Section Quantity:** 

**Knob Manufacturer Code:** 

82121

**Knob Manufacturer Part Number:** 

Α

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section rear

**Throw Quantity:** 

3 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Actuator knob

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

125.0 ac at sea level

**Switch Actuator Momentary Position:** 

Counterclockwise single actuator

**Switch Actuator Indexing Position Quantity:** 

8 single actuator

## **NSN 5930-00-009-4437**Rotary Switch - Page 2 of 2



Shaft Type:
Round, flatted, threaded hole single actuator
Criticality Code Justification:
Feat
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
5.0 amperes resistive load ac at sea level
Special Features:
Item must comply with requirements of desc production standard no. L00014; for navy nuclear propulsion plant products only
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Uns single mounting facility
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A052b0