

View Online at <https://aerobasegroup.com/nsn/5930-00-009-6762>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

3.500 inches

**Overall Height:**

6.531 inches

**Overall Width:**

2.812 inches

**Body Height:**

3.438 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.719 inches

**Longest Vertical Distance Between Mounting Centers:**

2.719 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

255.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

40.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+7.00 to 145.00 actuation point pounds per square inch and +1.00/+115.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw with scale and external deactuation point screw with scale

**Contact Stimulus Rating:**

1.00 differential point pounds per square inch and 30.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

115.0 dc at sea level second voltage

**Pressure Connector Type:**

Plain, threaded internal single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0