

View Online at <https://aerobasegroup.com/nsn/5930-00-009-6762>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

3.500 inches

Overall Height:

6.531 inches

Overall Width:

2.812 inches

Body Height:

3.438 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.719 inches

Longest Vertical Distance Between Mounting Centers:

2.719 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

255.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

40.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+7.00 to 145.00 actuation point pounds per square inch and +1.00/+115.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw with scale and external deactuation point screw with scale

Contact Stimulus Rating:

1.00 differential point pounds per square inch and 30.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

115.0 dc at sea level second voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0