NSN 5930-00-009-6783

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-009-6783

| Occasill Lawreths |
|---|
| Overall Length: |
| 5.938 inches |
| Overall Height: |
| 5.688 inches |
| Overall Width: |
| 2.406 inches |
| Body Length: |
| 4.750 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.194 inches and 0.197 inches |
| Distance Between Mounting Facility Centers: |
| 5.250 inches |
| Capillary Tube Length: |
| 120.0 inches |
| Bulb Length: |
| 3.188 inches |
| Bulb Diameter: |
| 0.812 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Mounting Method: |
| Flange and unthreaded hole |
| Features Provided: |
| Electrical access port |
| Contact Action Stimulus: |
| Increase |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 4.6 amperes resistive load fourth voltage |
| Contact Adjustability: |
| Deactuation point adjustable and actuation point adjustable |
| Contact Adjustment Range: |
| +140.00/+215.00 actuation point degrees fahrenheit and +140.00/+215.00 deactuation point degrees fahrenheit |
| Contact Adjustment Type: |
| External deactuation point screw and external actuation point screw |
| Contact Voltage Rating In Volts: |

550.0 dc at sea level third voltage

NSN 5930-00-009-6783 Thermostatic Switch - Page 2 of 2



| Media For Which Designed: |
|---------------------------|
| Gas or liquid |
| Style Designator: |
| Rectangular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A048b0