# NSN 5930-00-009-9896

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-009-9896

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.312 inches single mounting facility

## **Overall Length:**

2.743 inches

### **Overall Height:**

2.376 inches

### **Overall Width:**

2.376 inches

#### Shaft Diameter:

0.249 inches single actuator and 0.250 inches single actuator

#### Shaft Length:

1.000 inches single actuator

#### **Nonturn Device Radius:**

0.500 inches at 12: 00 o'clock

## Individual Section Quantity:

2

#### Nonturn Device Type:

Tab at 12: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

4 each section rear

#### **Throw Quantity:**

2 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

## **Thread Size:**

0.375 inches single mounting facility

## Contact Voltage Rating In Volts:

30.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

2 single actuator

## Shaft Type:

Round single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

## NSN 5930-00-009-9896

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 4.0 amperes resistive load dc at sea level Style Designator: Square wafer, panel mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0