NSN 5930-00-009-9993

Rotary Switch - Page 1 of 2

0.469 inches single mounting facility

Thread Class:

Thread Length:

2a single mounting facility



View Online at https://aerobasegroup.com/nsn/5930-00-009-9993

Hazardous Locations/environmental Protection: Explosion proof **Overall Length:** 3.469 inches **Overall Diameter:** 2.000 inches **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Nonturn Device Type:** Slotted bushing at 12: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section front **Throw Quantity:** 7 each section front **Mounting Method:** Threaded bushing single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.469 inches single mounting facility **Contact Voltage Rating In Volts:** 125.0 ac at sea level **Switch Actuator Indexing Position Quantity:** 8 single actuator **Terminal Type:** Tab w/screw **Contact Switching Action:** Makes before breaks each section front **Switch Actuator Positioning Increment:** 45.0 degrees single actuator **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

NSN 5930-00-009-9993

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A052b0