

View Online at <https://aerobasegroup.com/nsn/5930-00-010-6417>

**Hazardous Locations/environmental Protection:**

Explosion proof

**Overall Length:**

5.187 inches

**Overall Height:**

2.125 inches

**Overall Width:**

1.812 inches

**First Flat Length:**

0.500 inches single actuator

**Shaft Diameter:**

0.372 inches single actuator and 0.375 inches single actuator

**Shaft Length:**

0.860 inches single actuator and 0.890 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.188 inches single mounting facility

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

1.437 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

1.750 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

4 each section front

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Contact Voltage Rating In Volts:**

125.0 ac at sea level

**Switch Actuator Momentary Position:**

Clockwise single actuator

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, square, threaded hole single actuator

**Square Shaft Size:**

0.250 inches single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

30.0 amperes resistive load ac at sea level and 3.0 amperes lamp load ac at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0