## NSN 5930-00-013-1082

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-013-1082

Inre	ead Class:
2a	
Bod	ly Style:
Busl	hing mounted
Haza	ardous Locations/environmental Protection:
Mois	sture proof
Bod	ly Diameter:
0.94	0 inches
Bus	hing Length:
0.44	0 inches
Bod	ly Length:
1.14	0 inches
Actı	uator Diameter:
0.82	0 inches
Actı	uator Height:
0.94	0 inches
Actı	uator Color:
Whit	te single actuator
Illun	ninated Actuator Color:
Whit	te single actuator
Actu	uator Inscription:
Off s	single actuator
Max	imum Voltage Rating In Volts:
48.0	dc
Incle	osure Type:
Fully	/ enclosed
Mou	Inting Method:
Thre	eaded bushing
Feat	tures Provided:
Actu	lator seal
Thre	eady Qty Per Inch (tpi):
32	
Thre	ead Size:
0.46	9 inches
Non	pile-up Contact Arrangement:
2 po	le, single throw, double make, both positions maintained single switch u
Con	tact Load Current Rating At Maximum Rated Voltage:
2.00	0 amperes resistive dc and 2.000 amperes inductive dc
Thre	ead Series Designator:
Uns	
Terr	ninal Type And Quantity:
6 tał	o, solder lug

## NSN 5930-00-013-1082

Push Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0

