

View Online at <https://aerobasegroup.com/nsn/5930-00-013-7592>

**Thread Class:**

2b all threaded hole

**Hazardous Locations/environmental Protection:**

Dustproof and vibration resistant

**Overall Length:**

4.968 inches

**Body Diameter:**

Between 0.618 inches and 0.625 inches

**Body Length:**

3.593 inches

**Overall Diameter:**

1.750 inches

**Tempurature Sensing Element Type:**

Expanding shell

**Mounting Facility Circle Radius:**

0.765 inches

**Mounting Method:**

Flange and threaded hole

**Thready Qty Per Inch (tpi):**

40 all threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.112 inches all threaded hole

**Mounting Facility Pattern:**

Three position circular

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Wire lead

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage

**Contact Adjustability:**

Deactuation point adjustable, preset and

**Contact Adjustment Range:**

-100.00/+600.00 actuation point degrees fahrenheit and

**Contact Adjustment Type:**

External deactuation point screw

**Contact Stimulus Rating:**

85.00 actuation point degrees fahrenheit and

**Contact Voltage Rating In Volts:**

240.0 ac at sea level second voltage 115.0 dc at sea level third voltage

**Frequency In Hertz:**

60.0 first voltage60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Cylindrical w/flange

**Thread Series Designator:**

Unc all threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0