

View Online at <https://aerobasegroup.com/nsn/5930-00-013-7592>

Thread Class:

2b all threaded hole

Hazardous Locations/environmental Protection:

Dustproof and vibration resistant

Overall Length:

4.968 inches

Body Diameter:

Between 0.618 inches and 0.625 inches

Body Length:

3.593 inches

Overall Diameter:

1.750 inches

Tempurature Sensing Element Type:

Expanding shell

Mounting Facility Circle Radius:

0.765 inches

Mounting Method:

Flange and threaded hole

Thready Qty Per Inch (tpi):

40 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.112 inches all threaded hole

Mounting Facility Pattern:

Three position circular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Wire lead

Contact Load Current Rating:

5.0 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable, preset and

Contact Adjustment Range:

-100.00/+600.00 actuation point degrees fahrenheit and

Contact Adjustment Type:

External deactuation point screw

Contact Stimulus Rating:

85.00 actuation point degrees fahrenheit and

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage 115.0 dc at sea level third voltage

Frequency In Hertz:

60.0 first voltage60.0 second voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/flange

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0