

View Online at <https://aerobasegroup.com/nsn/5930-00-013-9136>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

Between 0.990 inches and 0.995 inches

Body Length:

1.000 inches

Actuator Style:

Round, stepped

Actuator Diameter:

Between 0.921 inches and 0.953 inches

Actuator Height:

0.688 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained and left position momentary and right position momentary

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Integral

Nonpile-up Contact Arrangement:

1 four throw, normally open, momentary action single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

20.000 amperes inductive dc

Test Data Document:

81349-mils9419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0