

View Online at <https://aerobasegroup.com/nsn/5930-00-013-9136>

**Body Style:**

Hole mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

Between 0.990 inches and 0.995 inches

**Body Length:**

1.000 inches

**Actuator Style:**

Round, stepped

**Actuator Diameter:**

Between 0.921 inches and 0.953 inches

**Actuator Height:**

0.688 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained and left position momentary and right position momentary

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Integral

**Nonpile-up Contact Arrangement:**

1 four throw, normally open, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes inductive dc

**Test Data Document:**

81349-mils9419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0