

View Online at <https://aerobasegroup.com/nsn/5930-00-013-9284>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

3.203 inches

**Shaft Diameter:**

0.266 inches 1st actuator

**Shaft Length:**

0.953 inches 2nd actuator

**Overall Diameter:**

1.424 inches

**Nonturn Device Radius:**

0.531 inches at 7: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Pin at 7: 00 o'clock

**Operating Temperature Range:**

-55.0 to 85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

6.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

13 1st actuator

**Shaft Type:**

Round, hollowed, slotted 1st actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees 2nd actuator

**Detent Rotational Torque Range:**

+20.000 to 45.000 inch-ounces 1st actuator

**Switch Actuator Stop Device Type:**

Fixed stop all actuators

**Contact Load Current Rating:**

10.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0