

View Online at <https://aerobasegroup.com/nsn/5930-00-013-9284>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.203 inches

Shaft Diameter:

0.266 inches 1st actuator

Shaft Length:

0.953 inches 2nd actuator

Overall Diameter:

1.424 inches

Nonturn Device Radius:

0.531 inches at 7: 00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Pin at 7: 00 o'clock

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

6.0 dc at sea level

Switch Actuator Indexing Position Quantity:

13 1st actuator

Shaft Type:

Round, hollowed, slotted 1st actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

30.0 degrees 2nd actuator

Detent Rotational Torque Range:

+20.000 to 45.000 inch-ounces 1st actuator

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

10.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0