

View Online at <https://aerobasegroup.com/nsn/5930-00-013-9506>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Overall Length:**

0.562 inches

**Overall Height:**

1.856 inches

**Overall Width:**

0.546 inches

**Bushing Length:**

Between 0.458 inches and 0.478 inches

**Body Length:**

0.562 inches

**Body Width:**

0.546 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.243 inches

**Actuator Height:**

Between 0.655 inches and 0.719 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

115.0 dc

**Mounting Surface To Terminal End Distance:**

0.701 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.000 amperes inductive dc

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0