NSN 5930-00-013-9564

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-013-9564 **Body Style:** Hole mounted **Overall Length:** 0.560 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.188 inches **Overall Width:** 0.200 inches **Body Length:** 0.560 inches **Body Width:** 0.200 inches **Body Height:** 0.700 inches **Actuator Style:** Round **Actuator Free Position Height:** 0.320 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 1.0 ounces **Switch Actuating Force:** 5.0 ounces **Actuator Movement:** Between 0.020 pretravel inches and 0.008 overtravel inches and 0.002 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 7.000 amperes resistive dc and 4.000 amperes inductive dc and 7.000 amperes resistive ac and 4.000 amperes inductive ac **Terminal Type And Quantity:** 3 wire lead Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5930-00-013-9564 Sensitive Switch - Page 2 of 2



Fiig:

A053a0