

View Online at <https://aerobasegroup.com/nsn/5930-00-013-9784>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.520 inches

**Overall Height:**

1.740 inches

**Overall Width:**

2.120 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.970 inches single actuator

**Unthreaded Mounting Hole Diameter:**

0.189 inches single mounting facility

**Individual Section Quantity:**

2

**Knob Specificational Markings:**

Arrow

**Longest Horizontal Distance Between Mounting Centers:**

2.120 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.120 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 2nd section rear

**Throw Quantity:**

3 2nd section rear

**Mounting Method:**

Bracket single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes 2nd section rear

**Switch Actuator Positioning Increment:**

90.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

7.5 amperes resistive load highest ac voltage rating at sea level

**Style Designator:**

Tap, circuit selector

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0