# NSN 5930-00-014-6518



Pressure Switch - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5930-00-014-6518
Thread Class:
2b single pressure connection
Inside Diameter:
0.438 inches single connection
Hazardous Locations/environmental Protection:
Oiltight
Overall Length:
5.750 inches
Overall Height:
6.625 inches
Overall Width:
2.750 inches
Body Length:
4.750 inches
Body Width:
2.500 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Distance Between Mounting Facility Centers:
5.250 inches
Pressure Switch Type:
Gage
Mounting Method:
Bracket and unthreaded hole
Thready Qty Per Inch (tpi):
20 single pressure connection
Contact Action Stimulus:
Increase

**Thread Size:** 

0.438 inches single pressure connection

**Mounting Facility Pattern:** 

Two position in-line

**Nonpile-up Contact Arrangement:** 

1 pole, single throw, normally open, momentary action

**Sensing Element Burst Pressure:** 

200.00 pound

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

9.6 amperes resistive load fourth voltage

**Contact Adjustability:** 

Deactuation point adjustable and actuation point adjustable

# NSN 5930-00-014-6518

Pressure Switch - Page 2 of 2



Contact Adjustment Range
--------------------------

+16.00 to 160.00 actuation point pound and +16.00/+160.00 deactuation point pound

## **Contact Adjustment Type:**

External deactuation point knob and external actuation point knob

## **Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

## **Pressure Connector Type:**

Plain, threaded internal single connection

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Rectangular w/bracket

**Thread Series Designator:** 

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A048b0