

View Online at <https://aerobasegroup.com/nsn/5930-00-014-6520>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.500 inches

Overall Height:

8.750 inches

Overall Width:

2.781 inches

Body Height:

2.500 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Longest Horizontal Distance Between Mounting Centers:

2.125 inches

Intermediate Horizontal Distance Between Mounting Centers:

3.625 inches

Temperature Sensing Element Type:

Bulb

Operating Temperature Rating:

245.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

9.6 amperes resistive load third voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+140.00 to 215.00 actuation point degrees fahrenheit and +140.00/+215.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External actuation point hex nut and external deactuation point hex nut

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular w/mounting lugs

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0