

View Online at <https://aerobasegroup.com/nsn/5930-00-014-6520>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

5.500 inches

**Overall Height:**

8.750 inches

**Overall Width:**

2.781 inches

**Body Height:**

2.500 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.125 inches

**Intermediate Horizontal Distance Between Mounting Centers:**

3.625 inches

**Temperature Sensing Element Type:**

Bulb

**Operating Temperature Rating:**

245.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Obtuse triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action

**Terminal Type:**

Screw

**Contact Load Current Rating:**

9.6 amperes resistive load third voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+140.00 to 215.00 actuation point degrees fahrenheit and +140.00/+215.00 deactuation point degrees fahrenheit

**Contact Adjustment Type:**

External actuation point hex nut and external deactuation point hex nut

**Contact Voltage Rating In Volts:**

550.0 dc at sea level fourth voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Rectangular w/mounting lugs

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0