## NSN 5930-00-014-6520

Thermostatic Switch - Page 1 of 2

Gas



View Online at https://aerobasegroup.com/nsn/5930-00-014-6520

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.500 inches
Overall Height:
8.750 inches
Overall Width:
2.781 inches
Body Height:
2.500 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Longest Horizontal Distance Between Mounting Centers:
2.125 inches
Intermediate Horizontal Distance Between Mounting Centers:
3.625 inches
Tempurature Sensing Element Type:
Bulb
Operating Tempurature Rating:
245.0 degrees fahrenheit
Mounting Method:
Bracket and unthreaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Obtuse triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
9.6 amperes resistive load third voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+140.00 to 215.00 actuation point degrees fahrenheit and +140.00/+215.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point hex nut and external deactuation point hex nut
Contact Voltage Rating In Volts:
550.0 dc at sea level fourth voltage
Media For Which Designed:

## NSN 5930-00-014-6520

Thermostatic Switch - Page 2 of 2



Style	Design	nator:

Rectangular w/mounting lugs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0