NSN 5930-00-015-1255

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-015-1255

view Offiline at https://aerobasegroup.com/hish/0330-00-013-1200
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
3.090 inches
Overall Width:
0.938 inches
Body Length:
3.090 inches
Body Width:
0.766 inches
Body Height:
1.646 inches
Case Material:
Metal
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.437 inches
Actuator Style:
Round
Actuator Diameter:
0.187 inches
Actuator Height:
0.402 inches
Maximum Voltage Rating In Volts:
230.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 inch-ounces
Switch Actuating Force:
98.0 ounces
Actuator Movement:
0.125 pretravel inches and 0.312 overtravel inches and 0.438 differential inches
Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes motor dc and 10.000 amperes resistive ac and 10.000 amperes inductive ac and 2.000 amperes lamp ac and 3.500 amperes motor ac

NSN 5930-00-015-1255

Sensitive Switch - Page 2 of 2



inread Series Designator:
Unc
Terminal Type And Quantity:
6 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A053a0