## NSN 5930-00-015-3542

**Hazardous Locations/environmental Protection:** 

Dustproof

**Overall Length:** 

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-015-3542

| 1.250 inches  |
|---|
| Overall Height:   |
| 0.406 inches  |
| Overall Width:  |
| 0.406 inches  |
| Body Length:  |
| 0.776 inches  |
| Body Width:   |
| 0.344 inches  |
| Body Height:  |
| 0.250 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.140 inches  |
| Distance Between Mounting Facility Centers:   |
| 1.000 inches  |
| Tempurature Sensing Element Type:   |
| Internal sensor   |
| Mounting Method:  |
| Bracket and unthreaded hole   |
| Contact Action Stimulus:  |
| Increase  |
| Mounting Facility Pattern:  |
| Two position in-line  |
| Nonpile-up Contact Arrangement:   |
| 1 pole, single throw, normally open, momentary action                                     |
| Terminal Type:  |
| Tab, solder lug   |
| Contact Load Current Rating:  |
| 2.5 amperes resistive load single voltage   |
| Contact Adjustability:  |
| Deactuation point not adjustable and actuation point not adjustable                       |
| Contact Stimulus Rating:  |
| 212.00 actuation point degrees fahrenheit and 208.00 deactuation point degrees fahrenheit |
| Contact Voltage Rating In Volts:  |
| 115.0 ac at sea level single voltage  |
| Frequency In Hertz:   |
| 60.0 single voltage   |
| Media For Which Designed:   |
| Gas   |

## NSN 5930-00-015-3542

Thermostatic Switch - Page 2 of 2



| Stv | e | Des | iar  | nato | r: |
|-----|---|-----|------|------|----|
| ,   | _ |     | . ສ. |      |    |

Rectangular w/bracket

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0