

View Online at <https://aerobasegroup.com/nsn/5930-00-017-4498>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant and dustproof and moisture resistant and oiltight

Overall Length:

0.850 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.069 inches

Overall Width:

0.320 inches

Body Length:

0.850 inches

Body Width:

0.320 inches

Body Height:

0.688 inches

Unthreaded Mounting Hole Diameter:

0.112 inches

Actuator Style:

Round

Actuator Diameter:

0.109 inches

Actuator Height:

0.069 inches

Actuator Free Position Height:

0.350 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Pile-up Contact Form Arrangement:

1z single position

Switch Release Force:

8.0 ounces

Switch Actuating Force:

Between 12.0 ounces and 24.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.010 differential inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0