

View Online at <https://aerobasegroup.com/nsn/5930-00-018-0921>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Driptight

Overall Length:

0.458 inches

Overall Height:

1.898 inches

Overall Width:

0.354 inches

Bushing Length:

Between 0.458 inches and 0.478 inches

Body Length:

0.562 inches

Body Width:

0.354 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.240 inches and 0.246 inches

Actuator Height:

Between 0.655 inches and 0.719 inches

Actuator Position-action Relationship:

Center position maintained and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0