

View Online at <https://aerobasegroup.com/nsn/5930-00-018-1305>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

1.120 inches

Overall Width:

0.620 inches

Bushing Length:

0.470 inches

Body Length:

1.120 inches

Body Width:

0.620 inches

Body Height:

0.910 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

0.245 inches

Actuator Height:

1.050 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position locked in

Maximum Voltage Rating In Volts:

230.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes resistive dc and 6.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0