NSN 5930-00-018-3447

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5930-00-018-5447
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
8.750 inches
Overall Height:
3.906 inches
Overall Width:
3.406 inches
First Flat Length:
0.875 inches single actuator
Shaft Diameter:
0.375 inches single actuator
Shaft Length:
5.375 inches single actuator
Individual Section Quantity:
6
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
A
Knob Specificationial Markings:
White arrow symbol
Longest Horizontal Distance Between Mounting Centers:
2.281 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.281 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
1 each section rear
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
20 single mounting facility

Thread Size:

0.250 inches single mounting facility

NSN 5930-00-018-3447Rotary Switch - Page 2 of 2



Contact Voltage Rating In Volts:
500.0 ac at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Shaft Type:
Round, parallel flatted, threaded hole single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
Contact Load Current Rating: 30.0 amperes resistive load dc at sea level
_
30.0 amperes resistive load dc at sea level
30.0 amperes resistive load dc at sea level Special Features:
30.0 amperes resistive load dc at sea level Special Features: First spacer blank
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator:
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator:
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility Shelf Life:
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility Shelf Life: N/a
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility Shelf Life: N/a
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility Shelf Life: N/a Unit Of Measure:
30.0 amperes resistive load dc at sea level Special Features: First spacer blank Style Designator: Tap, circuit selector Thread Series Designator: Unc single mounting facility Shelf Life: N/a Unit Of Measure: Demilitarization: