NSN 5930-00-018-5508

Rotary Switch - Page 1 of 2



30-00-018-5508

View Online at https://aerobasegroup.com/nsn/593
Thread Class:
2a single mounting facility
Thread Length:
0.250 inches single mounting facility
Overall Length:
2.125 inches
Overall Height:
1.100 inches
Overall Width:
0.940 inches
Shaft Diameter:
0.250 inches single actuator
Shaft Length:
0.875 inches single actuator
Nonturn Device Radius:
0.375 inches at 9: 00 o'clock
Individual Section Quantity:
2
Nonturn Device Type:
Tab at 9: 00 o'clock
Switch Contact Basic Design:
Nonpile-up nonsymmetrical
Pole Quantity:
1 each section rear
Throw Quantity:
6 each section rear
Mounting Method:
Threaded bushing single mounting facility
Thread Size:
0.375 inches single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Switch Actuator Indexing Position Quantity:
8 single actuator
Shaft Type:
Round single actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:

30.0 degrees single actuator

NSN 5930-00-018-5508

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

500.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0