

View Online at <https://aerobasegroup.com/nsn/5930-00-018-8187>

Hazardous Locations/environmental Protection:

Moisture resistant and salt spray resistant and shock resistant and vibration resistant

Overall Diameter:

1.156 inches

Body Thickness:

0.088 inches

Unthreaded Mounting Hole Diameter:

0.093 inches single mounting facility

Distance Between Mounting Facility Centers:

0.814 inches single mounting facility

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

6 single section rear

Mounting Method:

Strut single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Contact Load Current Rating:

750.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Switch section, rotary

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0