# NSN 5930-00-019-1448

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-019-1448

#### Body Style:

Hole mounted

#### Hazardous Locations/environmental Protection:

Dustproof

### **Overall Length:**

0.960 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

#### **Overall Height:**

0.749 inches

#### **Overall Width:**

0.250 inches

#### Body Length:

0.781 inches

#### Body Width:

0.250 inches

# Body Height:

Body Height.

# 0.359 inches

**Unthreaded Mounting Hole Diameter:** 

0.088 inches

#### **Actuator Style:**

Leaf

### Actuator Width:

0.160 inches

### **Actuator Free Position Height:**

0.530 inches

### Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

### Inclosure Type:

Fully enclosed

### **Mounting Method:**

Threaded stud

# Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

### Switch Release Force:

0.5 ounces

## Switch Actuating Force:

6.0 ounces

# Actuator Movement:

Between 0.094 pretravel inches and 0.031 overtravel inches and 0.030 differential inches

# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

# NSN 5930-00-019-1448

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0