NSN 5930-00-019-3095

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-019-3095

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Explosion proof and watertight

Overall Length:

1.625 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section front

Throw Quantity:

3 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Rotor Through Connection Quantity:

3 single section

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Switch Actuator Positioning Increment:

36.0 degrees single actuator

NSN 5930-00-019-3095

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

1.0 amperes resistive load ac at sea level

Style Designator:

Snap or line

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0