

View Online at <https://aerobasegroup.com/nsn/5930-00-020-2983>

**Overall Length:**

7.063 inches

**Outside Diameter:**

0.250 inches single connection

**Overall Height:**

2.625 inches

**Overall Width:**

4.500 inches

**Mounting Slot Width:**

0.344 inches

**Body Length:**

5.563 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.875 inches

**Longest Vertical Distance Between Mounting Centers:**

5.875 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Slot and surface

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

4800.00 pounds per square inch gage

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position diagonal

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

2.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+190.00 to 3200.00 actuation point pounds per square inch gage and +160.00/+3170.00 deactuation point pounds per square inch gage

**Contact Adjustment Type:**

Internal deactuation point screw and internal actuation point screw

**Contact Stimulus Rating:**

15.00 differential point pounds per square inch gage and 30.00 differential point pounds per square inch gage

**Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded external single connection

**Frequency In Hertz:**

60.0 single voltage

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0