

View Online at <https://aerobasegroup.com/nsn/5930-00-020-3602>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.687 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.216 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.625 inches single actuator

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

24 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0