NSN 5930-00-020-9474

Rotary Switch - Page 1 of 2

Thread Class:

7 single actuator **Shaft Type:**

Rectangular/square, threaded hole single actuator



View Online at https://aerobasegroup.com/nsn/5930-00-020-9474

2b single mounting facility **Hazardous Locations/environmental Protection:** Dustproof **Overall Length:** 5.532 inches **Overall Height:** 2.812 inches **Overall Width:** 2.812 inches **Shaft Length:** 0.750 inches single actuator **Individual Section Quantity: Knob Manufacturer Code:** 82121 **Longest Horizontal Distance Between Mounting Centers:** 2.297 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.297 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 7 each section rear **Mounting Method:** Threaded hole single mounting facility **Features Provided:** Actuator knob Thready Qty Per Inch (tpi): 24 single mounting facility **Thread Size:** 0.190 inches single mounting facility **Contact Voltage Rating In Volts:** 30.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:**

NSN 5930-00-020-9474Rotary Switch - Page 2 of 2



Square Shaft Size:
0.250 inches single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
10.0 amperes resistive load dc at sea leve
Precious Material And Location:
Contacts surfaces silver
Precious Material:
Silver
Style Designator:
Tap, circuit selector
Thread Series Designator:
Unc single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A052b0