

View Online at <https://aerobasegroup.com/nsn/5930-00-021-3707>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Driptight and dustproof and oiltight and watertight

Overall Height:

6.626 inches

Case Material:

Metal

Actuator Style:

Roller plunger

Actuator Free Position Height:

2.188 inches

Actuator Roller Diameter:

0.500 inches

Actuator Roller Width:

0.125 inches

Housing Height:

2.438 inches

Housing Length:

4.656 inches

Housing Width:

2.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.812 inches

Maximum Voltage Rating In Volts:

120.0 ac and 115.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

Switch Release Force:

20.0 ounces

Switch Actuating Force:

48.0 ounces

Actuator Movement:

0.094 pretravel inches and 0.250 overtravel inches and 0.047 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 2.000 amperes inductive dc and 10.000 amperes resistive ac and 40.000 amperes inductive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0