

View Online at <https://aerobasegroup.com/nsn/5930-00-021-3769>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Moisture proof

Overall Length:

2.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Overall Height:

1.040 inches

Overall Width:

0.687 inches

Body Length:

1.940 inches

Body Width:

0.687 inches

Body Height:

0.688 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Style:

Round

Actuator Height:

0.125 inches

Actuator Free Position Height:

0.984 inches

Actuator Adapter Style:

Leaf

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

0.8 ounces

Switch Actuating Force:

Between 1.0 ounces and 3.0 ounces

Actuator Movement:

Between 0.296 pretravel inches and 0.172 overtravel inches and 0.060 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

2.000 amperes resistive dc and 1.000 amperes inductive dc and 1.500 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0