## NSN 5930-00-021-6411

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-021-6411 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Submersible **Overall Length:** 1.340 inches **Overall Height:** 0.910 inches **Overall Width:** 2.890 inches **Bushing Length:** Between 0.450 inches and 0.490 inches **Body Length:** 1.340 inches **Body Width:** 0.910 inches **Body Height:** Between 1.090 inches and 1.130 inches **Actuator Style:** Round **Actuator Diameter:** Between 0.400 inches and 0.440 inches **Actuator Height:** Between 1.030 inches and 1.070 inches **Actuator Position-action Relationship:** Up position maintained and down position maintained and center position maintained **Actuator Position-locking Relationship:** Up position no locking action and down position no locking action and center position locked in **Maximum Voltage Rating In Volts:** 60.0 ac and 28.0 dc **End Application:** Submarine communications and antenna systems; aircraft: t-2, f-111, delta dart f-106, ov-10a and the u-2 airframe; submarine interior communication system **Inclosure Type:** Fully enclosed **Mounting Method:** 

32

**Thread Size:** 

Threaded bushing

Thready Qty Per Inch (tpi):

0.469 inches

# NSN 5930-00-021-6411

Toggle Switch - Page 2 of 2



#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

## **Criticality Code Justification:**

Feat

## **Contact Load Current Rating At Maximum Rated Voltage:**

20.000 amperes resistive dc and 12.000 amperes inductive dc and 5.000 amperes lamp dc and 15.000 amperes resistive ac and 15.000 amperes inductive ac and 4.000 amperes lamp ac

#### **Special Features:**

Weapon system essential

## **Test Data Document:**

81349-mils3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Thread Series Designator:**

Uns

## **Terminal Type And Quantity:**

6 screw

Shelf Life:

N/a

**Unit Of Measure:** 

#### **Demilitarization:**

No

Fiig:

A053a0