

View Online at <https://aerobasegroup.com/nsn/5930-00-021-6840>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Overall Length:**

0.781 inches

**Overall Height:**

1.640 inches

**Overall Width:**

0.672 inches

**Bushing Length:**

0.359 inches

**Body Length:**

0.781 inches

**Body Width:**

0.625 inches

**Body Height:**

0.656 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.347 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

0.734 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

48.0 ounces

**Switch Actuating Force:**

80.0 ounces

**Actuator Movement:**

Between 0.093 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 10.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0