NSN 5930-00-021-8399

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-00-021-8399

| Hazardous Locations/environmental Protection: |
|---|
| Vibration resistant |
| Overall Length: |
| 5.375 inches |
| Overall Height: |
| 5.500 inches |
| Operating Tempurature Rating: |
| Between -65.0 degrees fahrenheit and 250.0 degrees fahrenheit |
| Mounting Method: |
| Line and threaded bushing |
| Features Provided: |
| Hermetically sealed case |
| Thready Qty Per Inch (tpi): |
| 14 single threaded bushing |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.500 inches single threaded bushing |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action |
| Terminal Type: |
| Wire lead |
| Contact Load Current Rating: |
| 45.4 milliamperes resistive load first voltage |
| Contact Adjustability: |
| Actuation point not adjustable |
| Contact Stimulus Rating: |
| 10.00 actuation point gallons per minute |
| Contact Voltage Rating In Volts: |
| 32.0 dc at sea level second voltage |
| Media For Which Designed: |
| Liquid |
| Thread Series Designator: |
| Npt single threaded bushing |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No. |
| Fiig: |
| · ··a· |

A048b0