

View Online at <https://aerobasegroup.com/nsn/5930-00-022-3896>

Thread Class:

2a

Body Style:

Bushing mount

Overall Length:

1.312 inches

Overall Height:

2.280 inches

Overall Width:

0.870 inches

Bushing Length:

Between 0.406 inches and 0.530 inches

Body Length:

Between 1.296 inches and 1.328 inches

Body Width:

0.870 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.656 inches and 0.718 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

18.000 amperes resistive dc and 15.000 amperes inductive dc and 10.000 amperes lamp dc and 18.000 amperes resistive ac and 12.000 amperes inductive ac and 11.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0