

View Online at <https://aerobasegroup.com/nsn/5930-00-023-1800>

Inside Diameter:

0.375 inches all connections

Overall Length:

7.500 inches

Overall Height:

2.250 inches

Overall Width:

4.125 inches

Body Length:

3.125 inches

Body Height:

2.000 inches

Longest Horizontal Distance Between Mounting Centers:

3.438 inches

Longest Vertical Distance Between Mounting Centers:

2.500 inches

Pressure Switch Type:

Gage

Mounting Method:

Base and threaded hole

Thready Qty Per Inch (tpi):

32 all threaded hole

Contact Action Stimulus:

Increase

Thread Size:

0.750 inches second pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Screw

Contact Load Current Rating:

30.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+700.00 to 10000.00 actuation point pounds per square inch and +700.00/+10000.00 deactuation point pounds per square inch

Contact Adjustment Type:

External deactuation point knob with scale and external actuation point knob with scale

Contact Voltage Rating In Volts:

600.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas, liquefied

Style Designator:

Rectangular

Thread Series Designator:

Unc all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0