

View Online at <https://aerobasegroup.com/nsn/5930-00-023-6089>

Thread Class:

2a single mounting facility

Thread Length:

0.243 inches single mounting facility

Width Between Flats:

0.195 inches single actuator

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

1.000 inches

First Flat Length:

0.203 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.453 inches single actuator

Nonturn Device Radius:

0.406 inches at 1: 30 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 1: 30 o'clock

Operating Temperature Range:

-65.0 to 125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

3 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

30.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

50.0 milliamperes resistive load ac at altitude

Special Features:

Dummy contacts at positions 11 and 12, shaft drilled and tapped for 6-32 thd 0.125 in. Deep

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0