

View Online at <https://aerobasegroup.com/nsn/5930-00-023-6089>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.243 inches single mounting facility

**Width Between Flats:**

0.195 inches single actuator

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

1.000 inches

**First Flat Length:**

0.203 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.453 inches single actuator

**Nonturn Device Radius:**

0.406 inches at 1: 30 o'clock

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Pin at 1: 30 o'clock

**Operating Temperature Range:**

-65.0 to 125.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

3 single section rear

**Throw Quantity:**

2 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

30.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

50.0 milliamperes resistive load ac at altitude

**Special Features:**

Dummy contacts at positions 11 and 12, shaft drilled and tapped for 6-32 thd 0.125 in. Deep

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0