## NSN 5930-00-023-6097

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-023-6097

**Thread Class:** 

2a single mounting facility

Thread Length:

0.243 inches single mounting facility

Width Between Flats:

0.195 inches single actuator

**Overall Length:** 

1.025 inches

**Overall Height:** 

1.000 inches

**Overall Width:** 

0.937 inches

First Flat Length:

0.203 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.531 inches single actuator

**Individual Section Quantity:** 

1

## **Operating Tempurature Range:**

-65.0/+85.0 degrees celsius

## **Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

90.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, parallel flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-023-6097

Rotary Switch - Page 2 of 2



50.0 milliamperes resistive load ac at altitude

**Style Designator:** 

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0